

AUXILIARY ENGINE-DRIVEN

**STRIPE
HOG
SK8000**



STRIPE HOG – SK8000

Operating Pressure:	40,000 psi (2,750 bar)
Flow Rate:	12 gpm (45.4 lpm)
Fresh Water Capacity:	3,150 gallons (11,924 liters)
Waste Tank Capacity:	4,750 gallons (w/bladder bags) (17,980 liters)

**STRIPE
HOG
SK7500**



STRIPE HOG – SK7500

Operating Pressure:	40,000 psi (2,750 bar)
Flow Rate:	9 gpm (34 lpm)
Fresh Water Capacity:	1,220 gallons (4,618 liters)
Waste Tank Capacity:	1,950 gallons (w/bladder bags) (7,457 liters)

**STRIPE
HOG
SK5500**



STRIPE HOG – SK5500

Operating Pressure:	40,000 psi (2,750 bar)
Flow Rate:	7.3 gpm (27.6 lpm)
Fresh Water Capacity:	1,200 gallons (4,542 liters)
Waste Tank Capacity:	2,400 gallons (w/bladder bags) (9,085 liters)

**STRIPE
HOG
SK2000**



STRIPE HOG – SK2000

Operating Pressure:	40,000 psi (2,750 bar)
Flow Rate:	5.6 gpm (21.2 lpm)
Fresh Water Capacity:	600 gallons (2,271 liters)
Waste Tank Capacity:	1.950 gallons (w/bladder bags) (7,457 liters)



STRIPE HOG SH8000 - CHASSIS POWERED



STRIPE HOG SH7500 - CHASSIS POWERED

**STRIPE
HOG
SH5.2**



STRIPE HOG 5.2

Operating Pressure:	40,000 psi (2,750 bar)
Flow Rate:	5.2 gpm (19.6 lpm)
Fresh Water Capacity:	900 gallons (3,406 liters)
Waste Tank Capacity:	700 gallons (2,650 liters)



STRIPE HOG SK2000 - TRAILER MOUNTED FOR LOW CEILINGS / PARKING GARAGES

**STRIPE
HOG
SK3000**



STRIPE HOG – SK3000

Operating Pressure:	40,000 psi (2,750 bar)
Flow Rate:	7.3 gpm (27.6 lpm)
Fresh Water Capacity:	1,200 gallons (4,542 liters)
Waste Tank Capacity:	2,400 gallons (w/bladder bags) (9,085 liters)



COMES WITH THE HT2500 HOG RIDER



**ALSO SUPPORTS
THE HT1000SR
SELF-ROTATING
GROUND HOG!**

STRIPE HOG ADVANTAGES

DEWATERING SYSTEM

Our dewatering system filters collected debris water down to 100 micron, allowing you to dump the debris in a nearly dry state.

PATENTED BLADDER TANKS

Adding bladders inside of the water tanks allows them to double as dirty water tanks.

INSPECT JETS FROM INSIDE THE CAB

With our 5-axis Hog Arm, you can bend and rotate the blasting heads in such a way where you can safely inspect the water jets from within the truck's cab.

PLC - PROGRAMMABLE LOGIC CONTROLLER

Our SH8000 and SK8000 are equipped with dual HD Thru-Shaft motors which are capable of controlling the RPM of each blasting head independently. This allows you to increase your production rate and improve the profile on the surface. The new HD Thru-Shaft can accommodate spray bars from 6" to 22" for paint removal and 36" spray bars which gives you a 72" pass for rubber removal, surface prep and paint cleaning.

UNPARALLELED SUPPORT

We ship 98% of spare parts in the same day the order is received. We are also committed to answering all tech support phone calls within 10 minutes of your call 24/7 and in your language. Finally, our training team is committed to not only training your operators, but delivering relevant content and updates to keep your operators sharp year after year.



Visit us today
www.TheHog.com



HOG TUSK

Take your job from water blasting to grinding or both with The Hog Tusk! The Hog Tusk is a one-head attachment for Stripe Hog water blasting equipment that includes PCD grinding teeth and water blasting nozzles. The Hog Tusk uses 1/2 the water and gives you 2x the productivity making it the quickest and most effective way to remove your pavement markings and it is only available from HOG.



Our Learning Management System is the perfect place for your team members to receive certification and on-going training. Certified Operators minimize cost, maximize productivity, and optimize results.

www.TheHog.com



USA Office
3920 SE Commerce Ave.
Stuart, FL 34997
1-772-214-1714

European Office
Vavreckova 7074
760 01 Zlin, Czechia
+420 573 903 031

**STRIPE
HOG**



**PAINT REMOVAL
RUBBER REMOVAL
PAINT CLEANING
SURFACE CLEANING
ROAD RETEXTURING**

www.TheHog.com